

Accessories

Punch nut wrench for L series or 150 and 500 Series Bar shear stop for production shearing to 24" Bar Shear table extends the table from 3" to 12" Punch Rack holds up to 30 sets of Punches & Dies Steel bin catcher catches steel from bar shear Oversize die stand for punching over 2 1/4" round Oversize stripper for punching over 2 1/4" round Punch Table with Adjustable jig Grease bank for under cover lubrication Slug Type Angle Shear

Offset die stand for punching close to web *

Please specify: size of angle to be punched, largest diameter hole to be punched and distance out from web to center of hole



6 - 24" Brake * **Angle Shear Channel Shear Rod Shear Coper Notcher Square Notcher Pipe Notcher** Z & T Shear

* Check Station

Throat Depth 9"	
Tonnage 80	
2" hole in ½" 1 3/8" hole in ¾ 2 ¼" hole in 7/16	
## X 24" 1/4" x 24" 1/2" x 20" 3/4" x 10" 1" x 6"	
Angle Shear 90° - Slug Type - Server Cut	
Miter Angle 45° - Bar Shear - Slug Type 4" x 4" x ½" 4" x 4" x 3/8"	
Channel Shear 2", 3", 4", 5", 6"	
Rod Shear - Round (max) 1 1/4"	
Coper Notcher 90° (notcher station) (punch or power cavity) 3" x 3" x ½" 4" x 4" x ½"	
Square Notcher (notcher station) (punch or power cavity) 2" x 3" x 3/8" 3" x 3" x 3/8"	
Pipe Notcher Sched 40 or 80 (larger sizes on request) 1 1/4", 1 1/2", 2"	
Brake 6", 9", 14", 18", 2 capacity	4"
Strokes per minute - light material - at max capacity 50 9	
Hydraulics 2,000 psi	
Oil Capacity 16 gallons	
Motor - Standard 7 ½HP, 3 phase - Optional 7 ½HP, 1 phase	
Dimensions - Width - Length - Height Bar shear work ht. Punch table top ht. Cavity tabletop ht Notcher station working ht. 37" 46" 70" 29" 39 1/4" 41" 31"	
Weight (net) 3,100 lbs	

Uni-Hydro, Inc

310 E Gemini Ave Cosmos, MN 56228 800 - 328 - 0036